

Page #	Section	Specification	Request	Y/N
9 OF 74	Part III Scope of work	Each w/c position must seat a minimum of four (4) ambulatory passengers	On the cover sheet, you want to purchase 24 passenger buses. If you want 4 amb. Seats per w/c position, count a 30 passenger bus. Please clarify.	We need 24 ambulatory seats and 7 wheelchairs
10 of 74	1.1	General, Altoona Test	With the re-design of the F550 by Ford, Altoona testing will not be completed until this fall. Our Manufacturers are having to redesign the conversion body to comply with this change for ADA and Altoona. A passed test should be required before contract award. A summary of the test may not be available at time of bid opening.	TVT recognizes the Altoona testing will not be completed until this fall. An award will be made prior to the passed test, a summary of the test is required prior to delivery of the buses and as soon as is possible.
12 of 74	1.1.1	Dimensions and construction	<p>We do not offer laminated sidewall, rear wall, or roof.</p> <p>Side walls are attached to the side wall steel structure by using structural adhesive.</p> <p>The rear wall is a one-piece fiberglass rear cap.</p> <p>The roof is FRP. The FRP is glued to the Luna substrate using a hot melt glue system. Once the FRP is laid on the roof a weighted roller is used to ensure proper adhesion.</p>	Yes this is acceptable
13 of 74	1.1.6	Windows	<p>Not all windows are the same size, we will use 24" wide X 36" high window where a 36" x 36" window will not fit.</p> <p>Please confirm tempered safety glass is acceptable.</p> <p>Our window glass (glazing) is 1/8" thick</p> <p>Windows are AS-3</p> <p>Is this acceptable???</p>	Yes this is acceptable
17 of 74	1.7.1	Wheel housing shall be constructed of 14 ga. Stainless steel	Request you accept our standard One-piece 14 ga minimum galvanized steel wheel plates installed over the rear wheels for a flat floor layout. Introducing a dissimilar metal, (stainless) would promote galvanic corrosion.	Yes this is acceptable
17 of 74	1.6	Interior steps not to exceed 9" riser	With the re-design of the F550, the entrance step risers are 9.5" in height. Please accept this exception.	Yes this is acceptable
18 of 74	1.7.4	Splash guards	The front mud flaps can't be full width.	Yes this is acceptable
23 of 74	1.13.3	Front End	We do not offer metal or plastic front or rear bulkheads These areas are luan covered with grey padded vinyl.	Yes this is acceptable
25 of 74	1.15.1	Seat shall be power OEM seat	Request seat will be OEM There is not a power or air suspension seat option available aftermarket	Yes this is acceptable

EQUALS AND EXCEPTIONS AUGUST 15, 2017

29 of 74	1.23.1.1	Destination signs	See order form for the front and side Luminator Horizon LED destination sizes available.	See 1.23.1.1 regarding specs for the destination signs.
29 of 74	1.24	Equipped with EPCO Main Farebox M4	Request you accept Diamond Farebox model VX	Yes this is acceptable
32 of 74	2.2.3	Alternators shall be dual 12 volt 150 Amp	Request that you accept the single KEI 240A alternator or the OEM 225A alternator	Yes this is acceptable
40 of 74	2.17.1	Video Cameras	Please provide complete Seon camera specifications. The specification doesn't specify Camera type or size, hard drive storage capacity, any optional items which may be required.	See surveillance system information attached
39 of 74	2.15.3	Components, Interior heat	Request you consider add a supplemental coolant heater such as Webasto or Espar for rear heat	No this is not acceptable
41 of 74	3.2	Warranty: Coach 7Yr 200,000 mile, floor 7Yr 200,000 mile	Request that you accept our 5Yr. 100,000 mile warranty for the floor and coach manufacturer	No this is not acceptable
48 of 74	Attachment 2	30 passenger vans	On the cover sheet, you want to purchase 24 passenger buses. If you want 4 amb. Seats per w/c position, count a 30 passenger bus. Please clarify.	We need 24 ambulatory seats and 7 wheelchairs
31 of 74	1.25.2	Q-Straint QRT-360 with L-Track fitting, flange series flush mounted L-Track, and four tie downs per wheel chair position with storage bags shall be provided	Include AMF Bruns Systems and securements as part of the specifications.	The securements must be able to be interchangeable with the Q-Straint QRT-360 L-track fitting, flange series flush mounted L-Track matching the rest of our fleet.
22 of 74	1.13	Seating materials that meet Federal Motor Vehicle Safety Standard FMVSS 302 Fire Standards are acceptable.	Requests using the following language: Seat covering and padding shall cover the seat frame and meet FMVSS 302 and the Federal Register dated 10-20-1993 for flammability of interior material	Yes this is acceptable
23 of 74	1.14.1	Seating materials that meet Federal Motor Vehicle Safety Standard FMVSS 302 Fire Standards are acceptable.	Requests the addition to use Camira Rhino vinyl with a 5 year warranty.	If the Camira Rhino vinyl is equal to or better than the Freedman seating, 688 new port blue vinyl it is acceptable.

SURVEILLANCE SYSTEM INFO SHEET

Pre-wire only system info

Will the cables be supplied by the end user? YES _____ NO X
 If yes, provide info below.
 If no, specify system (mfg. & model) & provide info below. OR EQUAL TO
 Mfg. SEON DVR EXPLORER DX-HD
 Model 115724480284

System installation info

Will this install be matching an existing fleet? YES _____ NO X
 If yes, please include pictures.

DVR Capacity

Total GB storage required _____ 2GB Ram _____
 Mfg. _____ SEON
 Model 115724480284

DVR Location

1. Front overhead YES X
 (Requires a Front Storage option.)
 2. Specify other location _____
 (Requires engineering approval)

Camera Quantity

	Locations (max of 8)	Camera Type	Size (mm)	Specific Mounting Position Required
1 Behind driver facing entry door	X	SEON		
2 D/S facing front lift & entry door	X	SEON		
3 Front of vehicle facing rear installed under bulkhead (space permitting) OR installed on ceiling				
4 Front of vehicle facing out windshield installed under bulkhead (space permitting) OR installed on dash	X	SEON		
5 C/S facing driver	X	SEON		
6 D/S facing rear lift	X	SEON		
7 Rear wall facing forward				
8 D/S exterior facing rear	X	SEON		
9 C/S exterior facing rear	X	SEON		
10 Exterior facing rear				
11 Other - specify (Requires engineering approval)				

Inputs (Discreets) required?

If yes, check all that apply. YES _____ NO _____

1 Left turn	
2 Right turn	
3 Brake	
4 Backup	
5 Park Brake	
6 Running Lights	
7 Other - Specify (Requires engineering approval)	